

AXLE SET-UP SPECIFICATIONS/ TORQ

	Pinion Preload		Backlast	Torque	
	New (In lbs)	Used (in lbs)		Cap	RG Bolts
TOYOTA					
7.5 F or R	13-16	*6-8	*6-10	75	75
8" F or R	13-18	*6-8	*6-10	75	75
V6/Turbo/E-locker	15-20	*6-8	*6-10	75	75
T100/Tacoma	15-20	*6-8	*6-10	75	75
DANA					
Dana 30	15-18	*6-8	*6-10	60	55
Dana 44	15-20	*6-10	*6-10	60	55
Dana 60	20-30	*8-12	*6-10	80	110
Dana 70U	20-30	*8-12	*6-10	80	110
Dana 70	25-35	*12-16	*6-10	80	110
Dana 80	25-35	*8-12	*6-10	90	175
FORD					
Ford 8.8	15-20	*6-8	*8-15	60	60
Ford 9"	14-20	*6-8	*6-12	60	60
Ford 10.25	25-35	*8-12	*6-10	80	95
Ford 10.5	25-35	*8-12	*6-10	80	95
CHRYSLER					
Chrysler 8 1/4	*12-16	*6-10	*6-10	60	55
Chrysler 8 3/4	15-25	*6-10	*6-10	90	55
Chrysler 9 1/4	15-25	*6-10	*6-10	75	65
10.5 AAM	15-25	*8-12	*5-9	120	175
11.5 AAM	20-30	*8-12	*5-9	200	175
GM					
8.25 IFS	15-20	*7-10	*6-10	55	65
10 Bolt- 8.5	15-20	*7-10	*6-10	60	65
10 Bolt- 8.6	15-20	*7-10	*6-10	60	65
9.25 IFS	16-24	*8-12	*6-10	80	75
14 Bolt Semi-float 9.5	16-24	*8-12	*6-10	80	75
10.5 AAM w/out Pin Sup	15-25	*8-12	*5-9	120	175
11.5 AAM	20-30	*8-12	*5-9	200	175
12 Bolt Pass	15-20	*6-10	*6-10	55	60
12 Bolt Truck	14-18	*6-10	*6-10	55	60
14 Bolt Full Float w/ PS	25-35	*8-12	*6-10	135	120